



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification<sup>6</sup>:

F16L 9/18, 11/00, 5/10

A1

(11) International Publication Number:

WO 96/36831

(43) International Publication Date: 21 November 1996 (21.11.96)

(21) International Application Number: PCT/GB96/01129

(22) International Filing Date: 13 May 1996 (13.05.96)

(30) Priority Data:

9509861.2

16 May 1995 (16.05.95)

GB

(71) Applicant (for all designated States except US): BRITISH STEEL PLC [GB/GB]; 9 Albert Embankment, London SE1 7SN (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): PICKING, Kenneth, David [GB/GB]; 59 Gunnergate Lane, Marton, Middlesbrough, Cleveland TS7 8JA (GB).


(74) Agents: HEATH, Peter, William, Murray et al.; Fry Heath &amp; Spence, The Old College, 53 High Street, Horley, Surrey RH6 7BN (GB).

(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: ANNULAR SEPARATORS FOR DOUBLE WALLED PIPE STRUCTURES



## (57) Abstract

An annular bulkhead for separating the inner and outer generally coaxial pipes of a double walled pipe structure wherein the bulkhead is in the form of an annular resilient member dimensioned to fit, in use, the annular space between the pipes, wherein the annular resilient member is supported on each axial side thereof by means of at least partial annular rigid rings divided into separate segments and secured together through the resilient annular member.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

### **Annular Separators for Double Walled Pipe Structures**

This invention relates to annular separators for double walled pipe structures.

It has been proposed for transporting oil and/or gas from off-shore oil wells, to provide a pipeline formed of double walled pipes constructed from an outer and inner pipe of a generally coaxial disposition, the inner pipe being arranged to carry the oil or gas, which will usually be at an elevated temperature relative to ambient conditions, the inner and outer pipes being held apart by separators or bulkheads acting as seals between lengths of the annular space between the pipes, and the annular space between the inner pipe and the outer pipe being filled with hollow microspheres of alumino-silicate, for example, whereby thermally to insulate the oil or gas contained within the inner pipe, increase the strength of the structure and in certain circumstances enable the pipeline structure to float on the water surface. A pipeline formed of such inner and outer pipes can, with appropriate bulkheads between the two along their length, and interconnection to successive pipes by welding for example, act as a single compliant structure capable of being handled as a single pipe.

It has been proposed to use as such bulkheads an annular ring of

rubber or similar resilient material of generally rectangular cross-section sandwiched between two supporting steel rings on each side bolted together through the rubber.

One problem with such a structure is that when the pipeline is bent, such as when it is coiled on to a drum for carriage purposes, it deforms somewhat into an oval section, and the bulkheads can form distortions in the slightly oval bent or coiled pipe structure because of resistance to the oval deformation of the pipe structure.

It is an object of the present invention to overcome or at least substantially reduce the above mentioned problem.

In accordance with one aspect of the present invention there is provided an annular bulkhead for separating the inner and outer generally coaxial pipes of a double walled pipe structure wherein the bulkhead is in the form of an annular resilient member dimensioned to fit, in use, the annular space between the pipes, wherein the annular resilient member is supported on each axial side thereof by means of at least partial annular rigid rings divided into separate segments and secured together through the resilient annular member.

In one embodiment each rigid ring may be formed of steel, and may be separated into four equal segments around the bulkhead.

The segments of the annular steel rings may be staggered on each side so that separation between segments do not coincide with each other on both sides of the resilient member.

The invention includes within its scope a double walled pipe structure including an annular bulkhead as hereinabove defined separating an inner and an outer pipe.

In order that the invention may be more fully understood one embodiment thereof will now be described by way of example with reference to the accompanying drawings in which:-

Figure 1 illustrates in front elevation a bulkhead for a double walled pipe structure in accordance with the invention; and

Figure 2 is a sectional side elevation of part of a double walled structure showing the disposition of a bulkhead as shown in Figure 1.

Referring now to the drawings it will be seen that the bulkhead 1 comprises a rubber annular gasket member 2 of rectangular cross-section which fits in sealing fashion between the inner wall of an outer pipe 3, and the outer wall of an inner pipe 4 to separate the two in a generally coaxial disposition.

The resilient rubber sealing gasket 2 is supported on each side by a partially annular steel ring 5 segmented into four pieces 6, each slightly separated from the others and rounded at each end, each piece being connected by means of nuts and bolts 7, 8 to the steel support segment pieces 9 on the other axial side of the gasket member 2.

The segments 6, 9 of each steel ring 5, 10 are staggered with respect to the gasket member such that the gap between two segments on one side of the gasket member axially, corresponds generally with the centre position of a segment on the other side.

We have found that such an arrangement, whilst still providing good support, and hence separation of the inner and outer pipe with good sealing, is nonetheless of such radial flexibility as to be able to deform to an oval configuration corresponding to that taken up by the inner and outer pipes, when the double walled pipe structure is bent, for example

when it is disposed about a large transporting drum therefor.

It is to be understood that the foregoing is merely exemplary of bulkheads for double walled pipe structures in accordance with the invention and that modifications can readily be made thereto without departing from the true scope of the invention.

CLAIMS

1. An annular bulkhead for separating the inner and outer generally coaxial pipes of a double walled pipe structure wherein the bulkhead is in the form of an annular resilient member dimensioned to fit, in use, the annular space between the pipes, wherein the annular resilient member is supported on each axial side thereof by means of at least partial annular rigid rings divided into separate segments and secured together through the resilient annular member.
2. An annular bulkhead as claimed in Claim 1 wherein each rigid ring is formed of metal and is separated into a plurality of equal segments around the bulkhead.
3. An annular bulkhead as claimed in Claim 1 or 2 wherein the rigid ring is of steel and is separated into four equal segments around the bulkhead.
4. An annular bulkhead as claimed in Claim 1, 2 or 3 wherein the segments of the annular steel rings are staggered on each side so that separations between segments do not coincide with each other on opposite sides of the resilient member.
5. An annular bulkhead as claimed in any one of the preceding Claims wherein the segments on each side are slightly separated one from the others and are rounded at least each end.
6. An annular bulkhead as claimed in any one of the preceding Claims wherein the segments on opposite axial sides are secured together by bolts and nuts.

7. A double wall d pipe structure including an annular bulkhead as hereinb fore d scrib d.



1/1

FIG. 1.





FIG. 2.



## INTERNATIONAL SEARCH REPORT

Internat Application No

PCT/GB 96/01129

A. CLASSIFICATION F SUBJECT MATTER  
IPC 6 F16L9/18 F16L11/00 F16L5/10

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 F16L F17D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP,A,0 586 944 (DOYMA) 16 March 1994 see column 4, line 18 - column 4, line 56; figures 1,4 ---	1,2,6
A	US,A,4 569 210 (S.A. DE TELECOMM.) 11 February 1986 the whole description see figure 2 ---	1
A	EP,A,0 422 356 (ZEUNA-STÄRKER) 17 April 1991 see whole description ---	1
A	EP,A,0 537 603 (EBERSPÄCHER) 21 April 1993 see column 5, line 18 - column 6, line 26; figure 1 -----	1

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

14 August 1996

Date of mailing of the international search report

28.08.96

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3016

Authorized officer

Duerhammer, M

# INTERNATIONAL SEARCH REPORT

Information on patent family members

Internat

Application No

PCT/GB 96/01129

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-586944	16-03-94	DE-U- 9211978	12-11-92
US-A-4569210	11-02-86	FR-A- 2568385 EP-A- 0170948	31-01-86 12-02-86
EP-A-422356	17-04-91	DE-U- 8912161	07-02-91
EP-A-537603	21-04-93	DE-A- 4134466 DE-D- 59203667	22-04-93 19-10-95